

## Specifications

### Full Scale Capacity:

Standard 60,000 lb to 200,000 lb  
Custom up to 400,000 lb

### Concentrated Load Capacity (CLC):

Standard 50,000 lb to 70,000 lb  
Custom up to 100,000 lb

### Approvals:

NTEP Certified per H-44, Class III, 05-018  
Measurement Canada AM-5598

### Warranty:

One-year warranty on pivots, bearings, suspension and mounting parts of the corner assemblies  
Two-year weighbridge

Please refer to Warranty Statements starting on page 10



*Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.*

**Package includes:** Steel weighbridge; lever system; inboard transverse lever (for electronic conversion) is furnished unless outboard lever is specified at time of order; standard paint system is a high-performance epoxy base coat.

**Package does not include:** Foundation rebar; corrugated sheeting; pit angle coping; deck rebar; bumper plates; foundation bolts; assembly bolts; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

## Standard Features

- In-pit foundation
- Ideal for limited access locations
- Structural steel pipe lever system
- NTEP Certified 05-018
- Standard levers - 32.5 ton sectional rating
- Capacities to 400,000 lb
- Standard widths from 10 ft to 14 ft
- Standard profile 44.5 in
- Scale Options
- Load cell stand, steel deck option, pit angle coping, deck rebar, deck channel, bumper plates, foundation bolts, manhole frames and covers, conversion s-beam load cell(s), load cell mounting hardware, indicator, printer or other peripheral equipment

## APPROVALS



Measurement  
Canada  
Approved

## Additional Options Available

- Steel deck

# SURVIVOR® PT-M

Levertronic, Concrete Deck

## Length/Capacity

Length	Capacity	Est. Weight	Concrete Deck	Lever Sections	Section Capacity	Part #	Model	Price
<b>PT-M - 10 Foot Width</b>								
40 ft	50 tons	13,500 lb	5 in	3	32.5 tons	<b>90085</b>	540P10-C	Consult
50 ft	60 tons	16,900 lb	5 in	4	32.5 tons	<b>90086</b>	650P10-C	Consult
60 ft	100 tons	20,700 lb	6 in	4	32.5 tons	<b>90012</b>	1060P10-C	Consult
70 ft	100 tons	25,400 lb	6 in	5	32.5 tons	<b>90020</b>	1070P10-C	Consult
80 ft	100 tons	28,000 lb	6 in	5	32.5 tons	<b>90028</b>	1080P10-C	Consult
<b>PT-M - 11 Foot Width</b>								
40 ft	50 tons	14,400 lb	5 in	3	32.5 tons	<b>90078</b>	540P11-C	Consult
50 ft	60 tons	17,900 lb	5 in	4	32.5 tons	<b>90079</b>	650P11-C	Consult
60 ft	100 tons	21,900 lb	6 in	4	32.5 tons	<b>90080</b>	1060P11-C	Consult
70 ft	100 tons	26,800 lb	6 in	5	32.5 tons	<b>90082</b>	1070P11-C	Consult
80 ft	100 tons	29,600 lb	6 in	5	32.5 tons	<b>90083</b>	1080P11-C	Consult
<b>PT-M - 12 Foot Width</b>								
40 ft	50 tons	15,500 lb	5 in	3	32.5 tons	<b>90087</b>	540P12-C	Consult
50 ft	60 tons	19,100 lb	5 in	4	32.5 tons	<b>90088</b>	650P12-C	Consult
60 ft	100 tons	23,400 lb	6 in	4	32.5 tons	<b>90089</b>	1060P12-C	Consult
70 ft	100 tons	28,500 lb	6 in	5	32.5 tons	<b>90090</b>	1070P12-C	Consult
80 ft	100 tons	31,600 lb	6 in	5	32.5 tons	<b>90091</b>	1080P12-C	Consult

\*Lengths and widths for SURVIVOR PT-M scales are the I.D. dimensions of the scale pit

## Part Number/Price

Part #	Description	Price
<b>Scale Components</b>		
<b>Varied</b>	Rebar	Consult
<b>53782</b>	Corrugated sheeting, 26 gauge, galvanized 30 in x 144 in	Consult
<b>74277</b>	Corrugated sheeting, 26 gauge, galvanized 36 in x 120 in	Consult
<b>45073</b>	Corrugated sheeting, 29 gauge, galvanized 38 in x 120 in	Consult
<b>18799</b>	T-grip molding (minimum 10 ft length)	Consult
<b>Varied</b>	Manhole option	Consult
<b>Varied</b>	Slotted manhole option	Consult
<b>ITCM Kits</b>		
<b>17856</b>	ITCM Mount Assembly, 1,500 lb with load cell	Consult
<b>17857</b>	ITCM Mount Assembly, 2,000 lb with load cell	Consult
<b>17864</b>	ITCM Mount Assembly, 5,000 lb with load cell	Consult
<b>90753</b>	S-beam load cell stand, 34 in tall	Consult