

## Standard Features

- Mild or stainless steel frame, base and mast
- Diamond tread top plate, mild or stainless steel
- 500 lb, 1,000 lb, 2,000 lb capacity
- Large rubber wheels (not rated for IS) simplify movement on uneven floors
- Two IP67 Aluminum load cells
- Standard indicator mount with integral handles for the IQ plus 590-DC, 480/480 Plus Legend, and 482/482 Plus Legend

## Specifications

### End Load Capacity:

100% end loading

### mV/V Output:

2 mV/V

### Cable Length:

9 ft 10 in (3 m)

### Height:

Weighing platter: 4.5 in height when in weigh mode

### Column Height:

59 in

### Warranty:

DeckHand weldment five years, load cells two years, all other components one year

### Approvals:

NTEP Certified, CC 98-004, Class III, 2,500 d  
Measurement Canada approved, AM-5218



## APPROVALS



Measurement  
Canada  
Approved

## Part Number/Price

Part #	Overall Size (W x L x H)	Capacity	Est. Weight	Price
<b>Mild Steel</b>				
41293	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41294	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41295	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult
<b>Stainless Steel</b>				
41296	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41297	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41298	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult

## Options/Accessories

Part #	Description	Price
<b>Mild Steel</b>		
43376	500/1,000 lb mild steel ramp	Consult
43378	2,000 lb mild steel ramp	Consult
<b>Stainless Steel</b>		
43377	Ramp assembly, 500/1,000 lb, stainless steel, 25 in x 27 in	Consult
43379	Ramp assembly, 2,000 lb, stainless steel, 25 in x 27 in	Consult
Consult	Smooth top	N/C
<b>DeckHand Portable Scale Optional Indicator Mounts</b>		
41371	Mounting bracket for 320IS with battery option stainless steel	Consult

