RoughDeck® SS Stainless Steel Floor Scale



Specifications

End Load Capacity:

200% full scale at 1,000 lb 100% full scale at 2,000 lb and 5,000 lb 80% full scale at 10,000 lb

Cable Length:

20 ft (6.1 m) (for connecting junction box to indicator)

Threaded Eyebolt:

Hole (1/2-20NF) located in center of deck for easy lifting

Warranty:

RoughDeck SS weldment five years, load cells two years, all other components one year

Approvals:

NTEP CC 92-001, Class III 5,000d Measurement Canada AM-4827, Class III 5,000d AM-5301

Standard Features

- · Rugged non-corrosive design
- · 304 stainless steel construction
- · Rigid stainless steel channel frame
- Four stainless steel NTEP Certified shear-beam load cells
- 20 ft of SURVIVOR® EL147HE hostile environment load cell cable
- · Side access junction box
- TuffSeal® JB4SS stainless steel, NEMA Type 4X junction box with signal trim card
- · Smooth stainless steel deck
- Four adjustable stainless steel SUREFOOT™ support feet

APPROVALS



Measurement Canada Approved



Part Number/Price

		ALLIIOVED	AFFROVED		
Measurement Canada Approved Part #	Size (W x L x H)	Capacity	Est. Weight	Price	
191958 [†]	2.5 ft x 2.5 ft x 3.5 in	2,000 lb (1,000 kg)	173 lb	Consult	
191959†	3ft x 3ft x 3.5 in	1,000 lb (500 kg)	232 lb	Consult	
191960†	3ft x 3ft x 3.5 in	2,000 lb (1,000 kg)	232 lb	Consult	
191961	4ft x 4ft x 3.5 in	1,000 lb (500 kg)	375 lb	Consult	
191962	4ft x 4ft x 3.5 in	5,000 lb (2,500 kg)	375 lb	Consult	
191964	4ft x 4ft x 3.5 in	10,000 lb (5,000 kg)	490 lb	Consult	
191965	4ft x 5ft x 3.5in	5,000 lb (2,500 kg)	437 lb	Consult	
191966	4ft x 5ft x 3.5in	10,000 lb (5,000 kg)	567 lb	Consult	
191967	5ft x 5ft x 3.5in	5,000 lb (2,500 kg)	541 lb	Consult	
191968	5ft x 5ft x 3.5in	10,000 lb (5,000 kg)	696 lb	Consult	
191969	5ft x 7ft x 3.5in	5,000 lb (2,500 kg)	734 lb	Consult	
191970	5ft x 7ft x 3.5in	10,000 lb (5,000 kg)	929 lb	Consult	
	Canada Approved Part # 191958† 191959† 191960† 191961 191962 191964 191965 191966 191967 191968 191969	Canada Approved Part # Size (W x L x H) 191958† 2.5ft x 2.5ft x 3.5 in 191959† 3ft x 3ft x 3.5 in 191960† 3ft x 3ft x 3.5 in 191961 4ft x 4ft x 3.5 in 191962 4ft x 4ft x 3.5 in 191964 4ft x 4ft x 3.5 in 191965 4ft x 5ft x 3.5 in 191966 4ft x 5ft x 3.5 in 191967 5ft x 5ft x 3.5 in 191968 5ft x 5ft x 3.5 in 191969 5ft x 7ft x 3.5 in	Measurement Canada Approved Part # 191958† 2.5 ft x 2.5 ft x 3.5 in 2,000 lb (1,000 kg) 191959† 3 ft x 3 ft x 3.5 in 1,000 lb (500 kg) 191960† 3 ft x 3 ft x 3.5 in 2,000 lb (1,000 kg) 191961 4 ft x 4 ft x 3.5 in 1,000 lb (500 kg) 191962 4 ft x 4 ft x 3.5 in 5,000 lb (2,500 kg) 191964 4 ft x 4 ft x 3.5 in 10,000 lb (5,000 kg) 191965 4 ft x 5 ft x 3.5 in 5,000 lb (2,500 kg) 191966 4 ft x 5 ft x 3.5 in 10,000 lb (5,000 kg) 191967 5 ft x 5 ft x 3.5 in 5,000 lb (2,500 kg) 191968 5 ft x 5 ft x 3.5 in 10,000 lb (5,000 kg) 191969 5 ft x 7 ft x 3.5 in 5,000 lb (2,500 kg)	Measurement Canada Approved Part # Size (W x L x H) Capacity Est. Weight 191958† 2.5 ft x 2.5 ft x 3.5 in 2,000 lb (1,000 kg) 173 lb 191959† 3 ft x 3 ft x 3.5 in 1,000 lb (500 kg) 232 lb 191960† 3 ft x 3 ft x 3.5 in 2,000 lb (1,000 kg) 232 lb 191961 4 ft x 4 ft x 3.5 in 1,000 lb (500 kg) 375 lb 191962 4 ft x 4 ft x 3.5 in 5,000 lb (2,500 kg) 375 lb 191964 4 ft x 4 ft x 3.5 in 10,000 lb (5,000 kg) 490 lb 191965 4 ft x 5 ft x 3.5 in 5,000 lb (2,500 kg) 437 lb 191966 4 ft x 5 ft x 3.5 in 10,000 lb (5,000 kg) 567 lb 191967 5 ft x 5 ft x 3.5 in 5,000 lb (2,500 kg) 541 lb 191968 5 ft x 5 ft x 3.5 in 10,000 lb (5,000 kg) 696 lb 191969 5 ft x 7 ft x 3.5 in 5,000 lb (2,500 kg) 734 lb	

[†] Not recommended for use with pallet jacks

Options/Accessories

Part #	Description	Price
N/A	Access ramps, pit frames, bumper guards and portability frames available	See end of section for details
18778	Floor anchor plates, stainless steel (set of 2)	Consult
N/A	Four drilled deck holes for scale height adjustment	Consult
N/A	Top access junction box	+Consult list price add-on
N/A	Stainless steel deck with RLH35 welded-seal IP67 stainless steel FM approved load cells and hardware	+Consult list price add-on
N/A	Stainless steel deck with RL35082 hermetically sealed IP69K stainless steel cFMus approved load cells and hardware	+Consult list price add-on
28740	RoughDeck floor stand for indicator, 36.3 in high, stainless steel	Consult
Consult	Stainless steel diamond tread plate safety deck	Consult
N/A	Forklift channel option (up to $5 \text{ft} \times 7 \text{ft}$, $10,000 \text{lb}$, accommodates fork tines no larger than (W x H) $5 \text{in} \times 2 \text{in}$, fork entry is on opposite side of junction box location	+Consult list price add-on

398