BenchPro[™] BP-SR

Shipping Bench Scale with Roller Conveyor



Standard Features

- · Simple operation, easy to set up
- · Large six-digit backlight LCD display with 1 in (29 mm) characters protected by heavy-duty tempered glass
- · Powered USB HID point of sale interface plug and play USB interface provides power and communications to popular shipping software programs like FedEx Ship Manager and UPS Worldship
- Nine-pin RS-232 interface for use with USB HID POS, SMA, NCI, 3835, ECR, 8213 and EH
- · Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved

Specifications

Dynamic Response:

Response time for stable weight:

0 - 1,000d, 1,000 ms, maximum mean average 1,000d +, 1,500 ms, maximum mean average

Internal Resolution:

500,000 internal count minimum

Overload Protection:

Corner & center overload protection

Power:

In-line Power Supply (included)

Input: 100-240 VAC, +10% -15%, 3-wire w/ground Standard terminated with USA 3-prong plug Output: 12V at .1 Amps DC minimum Frequency: 50/60 Hz +/-3 Hz, standard Approvals: UL, CE, EN, CUL

USB HID: USB 2.0 full speed; Vendor ID: 1C19; Product ID: 0002

Construction:

Powder coat painted mild steel base plate and load bridge with stainless steel roller conveyor

Display:

Minimum key press life of 500,000 cycles, ABS plastic housing

6 annunciators to indicate Zero, Gross/Brutto, Net, W1/ W2/W3 multi-range 4 buttons: Units, Tare, On/Off, F1

RS-232 Cable (included):

10 ft DB 9-pin male to female, straight pass through and null modem

USB Cable (included):

46 in (1168.4 mm) A/B type USB cable

Approvals:

NTEP COC # 17-002 Canada Weights and Measures: AM - 6050

Warranty:

Two-year limited warranty



APPROVALS

Measurement Canada Approved

BenchPro[™] BP-SR

Shipping Bench Scale with Roller Conveyor

Part Number/Price


-						
Part #	Platform Capacity	Dimensions	Est. Weight	Price		
182996	150 x 0.05 lb (75 x 0.02 kg)	12 x 16 in	41 lb	Consult		
182394	100 x 0.02 lb (50 x 0.01 kg)	18 x 18 in	77 lb	Consult		
182381	150 x 0.05 lb (75 x 0.02 kg)	18 x 18 in	77 lb	Consult		
182386	300 x 0.1 lb (150 x 0.05 kg)	18 x 18 in	77 lb	Consult		
182398	300 x 0.1 lb (150 x 0.05 kg)	20 x 20 in	94 lb	Consult		
182402	300 x 0.1 lb (150 x 0.05 kg)	24 x 24 in	131 lb	Consult		


Options/Accessories

Part #	Description	Est. Weight	Price
180901	Second Customer display, BenchPro BP-SR no keyboard with 68 in cable	4 lb	Consult
174784	Second Remote operator display, BenchPro BP-SR with 68 in cable	4 lb	Consult
183103	16 in (H) tabletop display post for use with second display, customer or remote operator	4 lb	Consult
178501	USB-RS-232 serial adapter	1 lb	Consult

Dimensions - Inches

	A	В	C	D
12 x 16	12	16	15.30	5.95
18 x 18	18	18	21.10	6.50
20 x 20	20	20	23.10	6.50
24 x 24	24	24	27.10	6.50





211