

EPSON® TM-U295

Ticket Printer



Standard Features

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- Functions in slave capacity, printing information sent via RS-232

APPROVALS



Specifications

Print Speed:

1.9 to 2.3 lines per second (5 x 7 character, 3 dot line spacing)

Column Capacity:

35/42 columns

Characters Per Line:

35 standard font

Print Area:

2.59 in W (65.8 mm W)

Character Formation:

5 x 7 and 7 x 7 dot matrix

Character Height:

0.11 standard font

Character Set:

Full 96-character ASCII; with software control, 32 international characters, 128 x 2 graphic characters

Line Spacing:

0.16 in (4.06 mm) software programmable in 1/60 in units

Print Head Life:

Approximately 100 million strokes/pin

Form Thickness:

Single-ply: 0.003 in to 0.009 in (0.08 mm to 0.23 mm)
Copy paper: 0.003 in to 0.014 in (0.08 mm to 0.36 mm)

Ribbon:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

Serial Interfaces:

RS-232 compatible (25-Pin D-sub)

Baud Rates:

1200, 2400, 4800, 9600, selectable

Parity:

7 or 8 bits, none, even or odd

Stop Bits:

1 or more

Handshaking:

DTR/DSR or XON/XOFF control selectable

Overall Dimensions:

(W x D x H): 7.08 x 7.49 x 3.99 in (180 x 190.5 x 101.5 mm)

Approvals:

UL listed, CSA certified, CE marked

Warranty:

One-year limited warranty (includes print head)

Part Number/Price

Part #	Description	Est. Weight	Price
23113	TM-U295 Ticket Printer, RS-232, 115/230 VAC with power supply, cool white	9 lb	Consult
35891	TM-U295 Ticket Printer, 115/230 VAC with RS-232 and power supply, 25 DB to blunt end cable, cool white	9 lb	Consult
33816	TM-U295 Ticket Printer, RS-232, 24 VDC, cool white	9 lb	Consult

Options/Accessories

Part #	Description	Price
29582	Protective dust cover	Consult
29584	Ink cartridge (purple) ERC-27	Consult
29583	Ink cartridge (black) ERC-27B	Consult
23112	Power supply	Consult
34344	Additional operating manual	Consult
72309	Power supply, 12 VDC vehicle cigarette plug	Consult
Cables		
15568	25-Pin D-sub male to 25-Pin D-sub male RS-232 serial interface cable	Consult
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
41279	25-Pin D-sub male to 9-Pin D-sub male, RS-232 with handshaking	Consult
32810	25-Pin D-sub male to 8-Pin D-sub male, RS-232 with handshaking	Consult
Consult*	Custom 20 mA/RS-232 serial interface cable	Consult

*Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.
Standard cable length is 5 ft. \$2.00 charge for each additional foot.