

### Standard Features

- Replacement foot, adapts to most floor scales
- Use with single-ended beams to provide large, flat, adjustable introduction surface
- Special neoprene rubber sandwich base gives high accuracy, linearity and repeatability



### Part Number/Price

Part #	Material	Thread Size	Base Ht.		Total Ht.		Diameter		Price
18756	Stainless steel	1/2-20 UNF	0.75 in	19.1 mm	2.62 in	66.5 mm	3.47 in	88.1 mm	Consult
39021	Mild steel	3/4-16 UNF-2B	0.875 in	22.3 mm	3.25 in	82.3 mm	4.40 in	111.76 mm	Consult
39022	Mild steel	3/4-16 UNF-2B	0.875 in	22.3 mm	4.06 in	103.1 mm	5.40 in	137.16 mm	Consult
110930	Mild steel	1-14 UNF	1.0 in	25.4 mm	4.06 in	103.1 mm	5.40 in	137.16 mm	Consult
42130	Stainless steel	M12			2.62 in	67 mm	3.47 in	88.1 mm	Consult

## Flintec™ Adjustable Rubber Foot

### Standard Features

- Designed for platform scales containing Flintec SLB load cell
- Blind hole introduction
- Low profile
- Height adjustable by rotation
- Includes spacer
- Stainless steel



### Part Number/Price

Part #	Foot Diameter		Load Cell Capacity	Price
<b>Flintec SLB, SB4, SB5, SB14 and SB6</b>				
46230	2.36 in	60 mm	200 lb-500 lb	Consult
77561	3.14 in	80 mm	1,000 lb-5,000 lb	Consult
<b>Flintec BK2</b>				
87096	3.140 in	80 mm	200 kg-2,000 kg	Consult