

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS

ITCM-Isolated Tension Cell Mount page 44**Specifications****Full Scale Output:**

2.0 mV/V

Output Resistance:350 (\pm 3) ohm**Input Resistance:**385 (\pm 5) ohm**Material/Finish:**

Stainless steel

Temperature:

Operating range

-40° F to 150° F (-40° C to 65° C)

Safe Overload:

150% full scale

Rated Excitation:

5-10 VDC (15 V maximum)

Combined Error:

0.05%

Insulation Resistance:

5,000 megohms

Seal Type:

Welded seal, IP67

Cable Length:

20 ft (6.1 m)

Cable Diameter:

0.200 polyurethane jacket

Cable Color Code:

Red+ Excitation
 Black.....- Excitation
 Green.....+ Signal
 White- Signal
 Bare..... Shield

Warranty:

One-year limited warranty

**Dimensions**

Picture is a representation of actual product

Rated Capacity	A	B	D	E
lb/in				
500-3,000	1/2-20 UNF	1.00	2.00	2.97
5,000-10,000	3/4-16 UNF	1.00	3.00	4.25
kg/mm				
226.8-1,360.8	1/2-20 UNF	25.4	50.8	75.4
2,268.0-4,536.0	3/4-16 UNF	25.4	76.2	102.9

Order Information

Load Rating		Part#	Est. Weight	Price
500 lb	226.8 kg	69326	2 lb	Consult
750 lb	340.0 kg	69327	2 lb	Consult
1,000 lb	453.6 kg	69328	2 lb	Consult
1,500 lb	680.4 kg	69329	2 lb	Consult
2,000 lb	907.2 kg	69330	2 lb	Consult
2,500 lb	1,134.0 kg	69331	2 lb	Consult
3,000 lb	1,360.8 kg	69332	2 lb	Consult
5,000 lb	2,268.0 kg	69333	4 lb	Consult
10,000 lb	4,536.0 kg	69334	4 lb	Consult

