




Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E
lb/in					
50-200	1/4-28UNF	0.50	1.05	2.00	2.50
kg/mm					
22.7-90.7	1/4-28UNF	12.7	19.1	50.8	63.5

Order Information

Load Rating		Part#	Est. Weight	Price
50 lb	22.7 kg	30044	2 lb	Consult
100 lb	45.4 kg	30045	2 lb	Consult
150 lb	68.0 kg	30046	2 lb	Consult
200 lb	90.7 kg	35787	2 lb	Consult



Interchangeable Products

RICE LAKE WEIGHING SYSTEMS
RL20000 page 120

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS
ITCM-Isolated Tension Cell Mount page 44

Specifications

Full Scale Output:
 3.0 mV/V (50 lb capacity, 2.0 mV/V)

Output Resistance:
 350 (± 3) ohm

Input Resistance:
 385 (± 5) ohm

Material/Finish:
 High-alloy steel, nickel plated

Temperature:
 Operating range
 -40° F to 150° F (-40° C to 65° C)

Safe Overload:
 150% full scale

Rated Excitation:
 5-10 VDC (15 V maximum)

Nonlinearity:
 0.03% full scale

Hysteresis:
 0.02% full scale

Insulation Resistance:
 5,000 megohms

Seal Type:
 Environmentally sealed, IP67

Cable Length:
 20 ft (6.1 m)

Cable Diameter:
 0.200 polyurethane jacket

Cable Color Code:
 Red + Excitation
 Black - Excitation
 Green + Signal
 White - Signal
 Bare Shield

Warranty:
 One-year limited warranty

Approvals:

