

BenchMark® SL

Light-capacity Bench Scales



Standard Features

- 304 stainless steel construction
- LifeGuard™ base design isolates load cell from overloads and shock loads for added durability
- Specially designed adjustable support feet provide exceptional traction and won't scratch surfaces
- NTEP Certified IP66 aluminum load cell

Specifications

Load Cell, NTEP Certified:

IP66 Aluminum and environmentally sealed

Output Impedance:

350 Ω

Maximum Overload:

200%

Overload Protection:

Shock-absorbing spider

Cable Length:

10 ft (3 m)

Compensated Temperature Range:

14° F to 104° F (-10° C to 40° C)

Warranty:

Two-year limited warranty

Approvals:

NTEP CC 95-072, Class III 5,000 d, FM,
Measurement Canada AM-5082, Class III 5,000 d

APPROVALS



Measurement
Canada
Approved



Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
18575*	2 lb (1 kg)	10 x 10 x 3.15 in	13 lb	Consult
18576	5 lb (2.5 kg)	10 x 10 x 3.15 in	13 lb	Consult
18577	10 lb (5 kg)	10 x 10 x 3.15 in	13 lb	Consult
18578	20 lb (10 kg)	10 x 10 x 3.15 in	13 lb	Consult
18579	30 lb (15 kg)	10 x 10 x 3.15 in	13 lb	Consult
32914	30 lb (15 kg)	12 x 12 x 3.25 in	14 lb	Consult
32913	50 lb (25 kg)	12 x 12 x 3.25 in	14 lb	Consult
35198	100 lb (50 kg)	12 x 12 x 3.25 in	14 lb	Consult

Options/Accessories

Part #	Description	Price
N/A	Ball transfer and roller conveyor top	See end of section for details
112044	12 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus® CW-90, CW-90X and 480 Legend Series	Consult
112045	18 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus® CW-90, CW-90X and 480 Legend Series	Consult
64576	Attachment bracket for IQ plus® 210 or 420 plus, 320IS (without battery option), 320IS plus (without battery option) and 480 Legend	Consult
22125	Additional operating manual	Consult

Dimensions

Part #	Capacity	Platform Size (L x W)	L1/W1	H
18575*	2 lb (1 kg)	10 x 10 in	10.25 in	3.15 in
18576	5 lb (2.5 kg)	10 x 10 in	10.25 in	3.15 in
18577	10 lb (5 kg)	10 x 10 in	10.25 in	3.15 in
18578	20 lb (10 kg)	10 x 10 in	10.25 in	3.15 in
18579	30 lb (15 kg)	10 x 10 in	10.25 in	3.15 in
32914	30 lb (15 kg)	12 x 12 in	12.25 in	3.25 in
32913	50 lb (25 kg)	12 x 12 in	12.25 in	3.25 in
35198	100 lb (50 kg)	12 x 12 in	12.25 in	3.25 in

*Non-NTEP or Measurement Canada approved

Note: 1"=25.4 mm

