Specifications

Capacity:

800 lb x 0.5 lb (363 kg x 0.2 kg) 1,200 lb x 0.5 lb (544 kg x 0.2 kg)

Power:

Eight EL-123 batteries per scale system, two per pad (included) Three AAA lithium batteries (included) for handheld controller

Construction:

Powder coated molded plastic and cast aluminum

Operating Temperature:

50° F to 95° F (14° C to 35° C)

Warranty:

Two-year limited warranty





Bed positioned on pads



Handheld controller with bed-rail mount

Standard Features

- Four lightweight, wireless scale pads
- Four wheel-stops and roll-up ramps
- Handheld controller with bed-rail mount
- · Optional rubber controller glove and lanyard

Part Number/Price

Part #	Model	Capacity	Price
158216	D1100-8	800 lb x 0.5 lb (363 kg x 0.05 kg)	Consult
157222	D1100-12	1,200 lb x 0.5 lb (544 kg x 0.02 kg)	Consult

Shipping Weight

Part #	Model #	L (in)	W (in)	H (in)	Package Wgt. (lb)	Dim Wgt. (lb)	Shipping Wgt. (lb)
158216	D1100-8	17	13	13	15	21	21
157222	D1100-12	17	13	13	15	21	21

Options/Accessories

Part #	Description	Price
158229	Lanyard	Consult
158230	Rubber controller glove	Consult

