

Intercom



Sub Station



Speaker Horn

Specifications: Sub Station

- Speaker:**
20 Ω, 2 1/2 in diameter
- Wiring:**
CAT5 to Ethernet adapter
- Communication:**
Hands free at substation, master is push-to-talk, release-to-listen
- Dimensions:**
4-11/16 H x 4-11/16 W x 2 in D
- Mounting:**
Flush mount into two-gang box in kiosk

Specifications: Speaker/Horn

- Power Handling Capacity:**
25 watts (continuous)
- Impedance:**
8 ohms direct
- Frequency Response:**
400-6,000 Hz
- Dispersion Angle:**
130°
- Sound Pressure Level:**
103 dB at rated output measured 4 ft on axis
- Dimensions:**
6.3 in bell x 6.1 in depth (160 mm x 155 mm)

Standard Features: Sub Station

- Moisture and puncture resistant speaker
- Three-layer steel baffle protects speaker from tampering
- Hands-free communication
- Unit fits standard two-gang electrical box
- Pigtail wires for connection to Ethernet adapter
- Weather and vandal resistant

Standard Features: Speaker/Horn

- High intelligibility, used for paging into large or high-noise areas
- All metal weatherproof construction designed for outdoor use
- Universal bracket
- Aluminum housing

Part Number/Price

Part#	Description	Price
119757	Intercom, sub station Ethernet TCP/IP, requires 119760	Consult
119760	Adaptor, intercom over TCP/IP	Consult

Options/Accessories

Part#	Description	Price
158974	Single channel amplifier for Ethernet intercom	Consult
181686	Speaker, Horn 8 ohm 103 db	Consult

Ethernet Serial Servers



Part Number/Price

Part#	Description	Price
159118	Ethernet serial server dual serial port (two-terminal blocks) one Ethernet 10/100 (RJ45) DIN rail mounting	Consult
161532	Ethernet serial server dual serial port (two-terminal blocks) one Ethernet 10/100 (RJ45) DIN rail mounting	Consult