

Minebea Intec Combics 2

Complete Scale



Application Note:

Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing, averaging, totalizing

Standard Features

- Amber backlit LCD display, 0.8 in, 13 segment
- External calibration routine
- RS-232C
- Numeric keypad (with two IDs) for entering identifier codes and preset tares
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer specific data records
- Two scale connections, analog or digital

Part Number/Price

| RLWS PN | Minebea PN | Dimensions | Capacity | Readability | Est. Weight | Price |
|-------------------------------------|------------------|------------|-----------------|-----------------------|-------------|---------|
| Mild Steel with CAISL2-U | | | | | | |
| 156409 | CAW2P1U-10CC-I | 10 x 10 in | 15 lb (6 kg) | 0.0005 lb (0.0002 kg) | 10 ft | Consult |
| 156414 | CAW2P1U-50DD-I | 12 x 12 in | 60 lb (30 kg) | 0.002 lb (0.001 kg) | 10 ft | Consult |
| 156420 | CAW2P1U-100EE-I | 18 x 18 in | 150 lb (60 kg) | 0.005 lb (0.002 kg) | 10 ft | Consult |
| 156423 | CAW2P1U-250GG-I | 24 x 24 in | 300 lb (150 kg) | 0.01 lb (0.005 kg) | 10 ft | Consult |
| Stainless Steel with CAIS2-U | | | | | | |
| 156424 | CAW2S1U-10CC-I | 10 x 10 in | 15 lb (6 kg) | 0.0005 lb (0.0002 kg) | 10 ft | Consult |
| 156425 | CAW2S1U-50DD-I | 12 x 12 in | 60 lb (30 kg) | 0.002 lb (0.001 kg) | 10 ft | Consult |
| 156426 | CAW2S1U-100EE-I | 18 x 18 in | 150 lb (60 kg) | 0.005 lb (0.002 kg) | 10 ft | Consult |
| 156427 | CAW2S4UR-250GG-I | 24 x 24 in | 300 lb (150 kg) | 0.01 lb (0.005 kg) | 10 ft | Consult |

Options/Accessories

| RLWS PN | Minebea PN | Description | Price |
|---------|------------|--|---------|
| 156440 | YDH01CWSUS | Post mount assembly for 10 x 10 in platforms, 13 in high | Consult |
| 156441 | YDH02CWSUS | Post mount assembly for 12 x 12 in platforms, 19 in high | Consult |
| 156442 | YDH03CWSUS | Post mount assembly for 18 x 18 in platforms, 29 in high | Consult |
| 171727 | YDH12CWSUS | Bench mount bracket | Consult |

Specifications

Supply Voltage:

9V

Power Requirements:

120-240 VAC, 17 W / 23 VA maximum

Indicator Housing:

AISI 304 stainless steel

Indicator Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in (302.3 x 188 x 89 mm)

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Net Weight:

5 lb (2.27 kg)

Warranty:

Two-year limited warranty

Accessories: one-year limited warranty