

Minebea Intec Midrics 2 Series

Midrics/Combics System

Specifications

- Power Supply:**
100 - 200 VAC, 50 - 60 Hz
- Readability:**
15,000 scale intervals
- Cable Length:**
1.5 to 6 m (varies by capacity)
- Warranty:**
Two-year limited warranty



Standard Features

- Painted versions have IP65 protection rating for industrial use
- 304 stainless steel versions have IP67/IP68 protection ratings
- Four adjustable feet, level indicator on LCE and NCE
- Midrics 2 with 10-key touch pad and application programs
- Midrics 2 application programs – counting, checkweighing, classification, totalizing, net-total formulation, animal weighing, percent weighing, neutral measurement
- Weighing ranges from 6 kg to 150 kg
- Accessories: user installed interface kits, printer, external battery pack, software tools, panel mount kit

Part Number/Price

RLWS PN	Minebea PN	Dimensions	Capacity	Readability	Cable Platform	Est. Weight	Price
Mild Steel with MIS2-U							
156428	MW2P1UE-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	10 ft	18 lb	Consult
156429	MW2P1UE-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	10 ft	22 lb	Consult
156430	MW2P1UE-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	10 ft	63 lb	Consult
156431	MW2P1URE-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	10 ft	118 lb	Consult
Stainless Steel with MIS2-U							
156432	MW2S1UE-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	10 ft	18 lb	Consult
156433	MW2S1UE-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	10 ft	22 lb	Consult
156434	MW2S1UE-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	10 ft	63 lb	Consult
156435	MW2S4URE-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	10 ft	118 lb	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	Consult
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	Consult
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	Consult