

Motoweigh® Integrator



Specifications

Construction:

Stainless steel

Control Panel Size:

16 in x 16 in x 8 in

Power Configuration:

115-230 VAC single phase, 50/60 Hz

Standard Features

Software

- Four levels of security
- Real-time statistical information
- Product report
- Statistical report
- Parameter report
- User report
- Store up to 1,000 different products
- Five zone classification
- Configurable reject output
- Conveyor control output

Control Panel

- 16 in x 16 in x 8 in stainless steel enclosure
- Panel mount 920i®
- 24VDC power supply
- 16 Opto 22 relays
- Terminal blocks for easy wiring

Options and Accessories

- One, three or five zone communication tower
- Audible alarm (non-washdown only)

Part Number/Price

| Part # | Main Systems | Price |
|--------|--|---------|
| 185800 | 920i panel mount with MotoWeigh software, without cord grips | Consult |
| 185801 | 920i panel mount with MotoWeigh software, with cord grips | Consult |
| Part # | Options / Accessories | Price |
| 185803 | Alarm communication tower | Consult |
| 185804 | Red communication tower | Consult |
| 185805 | Three zone communication tower | Consult |
| 185806 | Three zone and alarm communication tower | Consult |
| 185807 | Five zone communication tower | Consult |