

Interchangeable Products

TRANSCELL®
FAV—

Specifications

- Full Scale Output:**
2 mv/V
- Output Resistance:**
350 (± 3) ohm
- Input Resistance:**
415 (± 15) ohm
- Material/Finish:**
Anodized aluminum
- Temperature:**
Operating range:
0°F to 150°F (-18°C to 65°C)
- Seal Type:**
Environmentally sealed, IP66
- Safe Overload:**
150% of rated output
- Rated Excitation:**
10 VAC (15 V max)
- Combined Error:**
0.02% full scale
- Insulation Resistance:**
2,000 megohms
- Cable Length:**
5 ft (1.5 m)
- Cable Diameter:**
0.200 PVC jacket
- Cable Color Code:**
Green +Excitation
Black -Excitation
Red +Signal
White -Signal
- Max Platform Size:**
24 in x 24 in
- Warranty:**
One-year limited warranty
- Approvals:**
OIML
Ex (Available upon request)

APPROVALS



Available upon request



Picture is a representation of actual product

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I
kg/mm									
50-635 kg	174.0	122.0	60.0	62.5	43.0	19.0	30.0	7.0	M8-6
lb/in									
110.2-1,399.9 lb	6.85	4.80	2.36	2.46	1.69	0.74	1.18	0.27	M8-6

Order Information

Load Rating	Part#	Est. Weight	Price
50 kg	157478	5 lb	Consult
100 kg	157479	5 lb	Consult
150 kg	157480	5 lb	Consult
200 kg	157481	5 lb	Consult
250 kg	157482	5 lb	Consult
300 kg	157483	5 lb	Consult
500 kg	157484	5 lb	Consult
635 kg	157485	5 lb	Consult

