

Specifications

- Full Scale Output:**
1 mV/V
- Output Resistance:**
1,000 (±10) ohm
- Input Resistance:**
1,160 (± 15) ohm
- Material/Finish:**
Aluminum
- Temperature:**
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
0°F to 150°F (-18°C to 65°C)
- Seal Type:**
Environmentally sealed, IP65
- Safe Overload:**
150% full scale
- Rated Excitation:**
5-10 VDC
- Insulation Resistance:**
5,000 megohms
- Cable Length:**
1.5 m flat ribbon type, PVC
- Cable Color Code:**
Green +Excitation
Black -Excitation
Red +Signal
White -Signal
- Warranty:**
One-year limited warranty
- Approvals:**
NTEP
OIML (Available upon request)

APPROVALS



Available upon request



Picture is a representation of actual product

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I
kg/mm									
7.5	70	39	4.9	28	14	2.5	27.8	5.1	5.1
15	70	39	4.9	28	14	4.1	27.8	5.1	5.1
37.5	76.2	44.5	6	29.3	15	4.8	30	6.6	6.2
50	84.5	55.0	6.4	34	15	5.3	30	6.6	7.6
75	84.5	55.0	6.4	34	15	6.4	30	6.6	7.6
150	107.5	70.0	7.8	45.9	22.8	8	44.5	8.1	8.2

Order Information

Load Rating	Part#	Est. Weight	Price
7.5 kg	112921	1 lb	Consult
15 kg	186687	1 lb	Consult
37.5 kg	112922	1 lb	Consult
50 kg	112923	1 lb	Consult
75 kg	112924	1 lb	Consult
150 kg	112925	1 lb	Consult

