

Interchangeable Products

RICE LAKE WEIGHING SYSTEMS
RL20001HE page 124

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS
ITCM Isolated Tension Cell Mount..... page 46

Specifications

Full Scale Output:
2.0 mV/V

Output Resistance:
349-355 ohms

Input Resistance:
349-350 ohms

Material/Finish:
Stainless steel

Temperature:
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
0°F to 150°F (-18°C to 65°C)

Seal Type:
Welded-seal, IP68

Safe Overload:
150% full scale

Rated Excitation:
5- 10 V DC (15 V maximum)

Combined Error:
0.03% full scale

Insulation Resistance:
5,000 megohms

Cable Length:
20 ft (6.1 m)

Cable Diameter:
0.200 polyurethane jacket

Cable Color Code:
Red +Excitation
Black -Excitation
Green +Signal
White -Signal

Warranty:
One-year limited warranty

Approvals:
cFMus
NTEP

APPROVALS



Picture is a representation of actual product

Dimensions

Rated Capacity	A	B	D	E
lb/in				
500-3,000	1/2-20 UNF	1.00	2.00	3.00
5,000-10,000	3/4-16 UNF	1.00	3.50	4.75
kg/mm				
226.8-1,360.8	1/2-20 UNF	25.4	50.8	76.2
2,268.0-4,535.9	3/4-16 UNF	25.4	88.9	120.7

Order Information

Load Rating	Part#	Est. Weight	Price
NTEP Certified			
500 lb	36272	3 lb	Consult
750 lb	36273	3 lb	Consult
1,000 lb	36274	3 lb	Consult
1,500 lb	36275	3 lb	Consult
2,000 lb	36276	3 lb	Consult
2,500 lb	36277	3 lb	Consult
3,000 lb	36278	3 lb	Consult
5,000 lb	36279	4 lb	Consult
Non-NTEP Certified			
10,000 lb	36280	4 lb	Consult

