

Specifications

- Full Scale Output:**
2 mV/V ± 1%
- Output Resistance:**
706 (± 3.5) ohms
- Input Resistance:**
700 (± 20) ohms
- Material/Finish:**
Stainless steel
- Temperature:**
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
0°F to 150°F (-18°C to 65°C)
- Seal Type:**
Hermetically sealed, IP68
- Safe Overload:**
130% full scale
- Rated Excitation:**
5- 10 VDC (15 V maximum)
- Combined Error:**
0.03% full scale
- Insulation Resistance:**
5,000 megohms
- Cable Length:**
12 m (39.37ft)
- Cable Diameter:**
0.190 polyurethane jacket
- Cable Color Code:**
Blue +Excitation
Black -Excitation
White +Signal
Red -Signal
Green +Sense
Grey -Sense
- Warranty:**
One-year limited warranty
- Approvals:**
NTEP
OIML



APPROVALS



Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E	R
T/mm						
20	150.00	76.1	44.00	48.00	44.00	130.00
30	150.00	76.1	44.00	48.00	44.00	160.00
40	150.00	76.1	44.00	48.00	44.00	180.00
60	210.00	76.1	44.00	48.00	44.00	220.00
T/in						
20	5.90	3.00	1.73	1.89	1.73	5.11
30	5.90	3.00	1.73	1.89	1.73	6.30
40	5.90	3.00	1.73	1.89	1.73	7.08
60	8.27	3.00	1.73	1.89	1.73	8.66

Order Information

Load Rating	Part#	Est. Weight	Price
OIML C3			
20T	69312	6 lb	Consult
30T	69313	6 lb	Consult
40T	69314	10 lb	Consult
60T	125266	10 lb	Consult
NTEP Certified			
20T	106149	6 lb	Consult
30T	106150	6 lb	Consult
40T	106151	10 lb	Consult
60T	125265	10 lb	Consult

