

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS
EZ Mount 1 page 86

**DISCONTINUED
 LIMITED STOCK
 AVAILABLE**

Specifications

- Full Scale Output:**
3.0 mV/V
- Output Resistance:**
700 (± 5) ohm
- Input Resistance:**
770 (± 10) ohm
- Material/Finish:**
High-alloy steel, nickel plated
- Temperature:**
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
0°F to 150°F (-18°C to 65°C)
- Seal Type:**
Environmentally sealed, IP67

- Safe Overload:**
150% full scale
- Safe Sideload:**
100% full scale
- Rated Excitation:**
5-10 VDC (15 V maximum)
- Combined Error:**
0.02% full scale
- Non-Repeatability:**
0.02% full scale

- Insulation Resistance:**
5,000 megohms
- Cable Length:**
30 ft (9.1 m)
- Cable Diameter:**
0.200 polyurethane jacket (5,000 lb)
- Cable Color Code:**
Red +Excitation
Black -Excitation
Green +Signal
White -Signal

Warranty:
One-year limited warranty

Approvals:
cFMus
NTEP

APPROVALS



Dimensions

Picture is a representation of actual product

Rated Capacity	L	L1	L2	D	D1	D2	P	R
lb/in								
5,000	8.12	6.88	5.24	1.70	1.48	0.66	1.12	0.50
kg/mm								
2,268.0	206.3	174.8	133.1	46.5	41.0	16.8	28.5	12.7

Order Information

Load Rating	Part#	Est. Weight	Price
5,000 lb	42120	5 lb	Consult

