

**Weigh Module Available**

RICE LAKE WEIGHING SYSTEMS

**Paramounts® HE** ..... page 42

RICE LAKE WEIGHING SYSTEMS

**Paramounts® HS** ..... page 62**Specifications****Full Scale Output:**

2.0 mV/V

**Output Resistance:**

1,000 (± 2) ohm

**Input Resistance:**

1,100 (± 50) ohm

**Material/Finish:**

Stainless steel

**Temperature:**

Operating range

0°F to 150°F (-18°C to 65°C)

**Seal Type:**

Hermetically sealed, IP69K

**Safe Overload:**

200% full scale

**Safe Sideload:**

100% full scale

**Rated Excitation:**

5-10 VDC (15 V maximum)

**Nonlinearity:**

0 to -0.03% full scale

**Hysteresis:**

0 to +0.05% full scale

**Insulation Resistance:**

10,000 megohms

**Deflection at Capacity:**

0.008 in (0.15 mm) (2.3 kN)

**Cable Length:**

10 ft (3.1 m)

**Cable Diameter:**

0.196 polyurethane jacket

**Cable Color Code:**

Green +Excitation

Black -Excitation

White +Signal

Red -Signal

Yellow Shield

**Warranty:**

One-year limited warranty

**Approvals:**

OIML

**APPROVALS****Dimensions***Picture is a representation of actual product*

Rated Capacity	L	L1	L2	H	W	I	K	C
kN/in								
2.3	6.10	2.98	1.60	1.58	0.59	0.54	0.99	1.387
lb/mm								
520	155.0	75.7	40.6	40.1	15.0	0.54	25.1	35.0

**Order Information**

Load Rating	Part#	Est. Weight	Price	
2.3 kN	520 lb	<b>38215</b>	4 lb	Consult
Conduit adapter, 1/2-14 NPT	<b>17703</b>	1 lb	Consult	

