



CE RoHS

### DIMENSIONS

RATED CAPACITY	H	L	L1	L2	L3	L4	W	W1	T
<b>kg/mm</b>									
60-1,000	62.0	176.0	44.0	122.0	19.0	8.0	60.0	30.0	M8 Depth25
<b>lb/inches</b> (conversion of above dimensions)									
132.3-2,204.6	2.44	6.93	1.73	4.80	0.75	0.31	2.36	1.18	M8 Depth0.98

### SPECIFICATIONS

<b>Full Scale Output</b>	2.0 mV/V $\pm$ 0.25%	<b>Recommended Excitation</b>	10V (15V Maximum)
<b>Zero Balance</b>	$\pm$ 0.02 mV/V	<b>Reference Max. Platform Size</b>	600 x 700 mm
<b>Non-linearity</b>	$<$ $\pm$ 0.03%	<b>Insulation Resistance</b>	$>$ 2 [ 50V DC ] G $\Omega$
<b>Repeatability</b>	$<$ $\pm$ 0.02%	<b>Nominal Temperature Range</b>	-10°C to 50°C / 14°F to 122°F
<b>Hysteresis Error</b>	$<$ $\pm$ 0.02%	<b>Safe Overload</b>	150% of full scale
<b>Creep in 30 min.</b>	$<$ $\pm$ 0.03%	<b>Breaking Overload</b>	300% of full scale
<b>Input Resistance</b>	385 $\Omega$ $\pm$ 15	<b>Seal Type / IP Rating</b>	Welded Seal / IP68
<b>Output Resistance</b>	350 $\Omega$ $\pm$ 3	<b>Cable Color Code</b>	Exc+ Red      Exc- Black Sig+ Green    Sig- White    Shield Bare
<b>Element Material</b>	17-4PH Stainless Steel		

### PART NUMBER

Rated Capacity	Part No.	Weight (kg) Approx.
60kg.....	651KSCS-60kg.....	4.0
100kg.....	651KSCS-100kg.....	4.0
150kg.....	651KSCS-150kg.....	4.0
200kg.....	651KSCS-200kg.....	4.0
250kg.....	651KSCS-250kg.....	4.0
300kg.....	651KSCS-300kg.....	4.0
500kg.....	651KSCS-500kg.....	4.0
600kg.....	651KSCS-600kg.....	4.0
750kg.....	651KSCS-750kg.....	4.0
1t.....	651KSCS-1t.....	4.0

### AVAILABLE OPTIONS

- Aluminum version 108CA (page 55)

SINGLE POINTS