



Standard Features

- Electronically controlled load (ECL) self-diagnostic before internal repeatability test without an external weight in less than 1.5 minutes
- Internal calibration weight
- Impact shock detection
- Flow rate display
- RS-232C and USB bidirectional interface
- Password protection and anti-theft security slot
- GLP/GMP/ISO compliant to either AD-8127 printer or computer
- Transmits date, time, ID number, serial number, model, manufacturer and calibration data
- Rechargeable battery option for portability
- Counting, Percentage, Animal Weighing, Density, Statistical and Comparator Modes
- Super Hybrid Sensor Technology (SHS)
- Reverse backlit LCD display
- Optional glass breeze break
- Underhook weighing

Specifications

	GX-203A [^]	GX-303A [^]	GX-403A [^]	GX-603A [^]	GX-1003A [^]	GX-2002A
Part #	191691	191692	191693	191694	191695	191697
List Price	Consult	Consult	Consult	Consult	Consult	Consult
Capacity	220 g	320 g	420 g	620 g	1,100 g	2,200 g
Resolution	0.001 g	0.001 g	0.001 g	0.001 g	0.001 g	0.01 g
Operating Modes	Animal Weighing, Comparator Function, ACAI Counting, Percentage, Density Determination, Statistical Calculation					
Repeatability	0.001 g					0.01 g
Linearity	±0.002 g				±0.003 g	±0.02 g
Stabilization Time	Approx. 1 second					
Display Refresh	5 times per second/10 times per second/20 times per second					
Operating Temperature	41° F to 104° F (5° C to 40° C) RH less than 85% (no condensation)					
Pan Size	5 x 5 in (128 x 128 mm)					
Dimensions	(W x D x H) 8.3 x 12.5 x 3.7 in (212 x 317 x 93 mm)					
Weighing Chamber	3 in H (85 mm H)					
Est. Ship Weight	11 lb (5 kg)					
Power	120VAC adapter, Approx. 30VA					
Warranty	Five-year Limited Warranty					
Return Policy	A&D Weighing Standard Policy - restock fee may apply					
Gram	220 x 0.001 g	320 g x 0.001 g	420 x 0.001 g	620 x 0.001 g	1100 x 0.001 g	2200 x 0.01 g
Ounce (Avoir)	7.76 x 0.00005 g	11.29 x 0.00005 g	14.81 x 0.00005 g	21.86 x 0.00005 g	38.80 x 0.00005 g	77.6 x 0.0005 g
Pound	0.485 x 0.000005 g	0.705 x 0.000005 g	0.925 x 0.000005 g	1.366 x 0.000005 g	2.425 x 0.000005 g	4.85 x 0.00005 g
Pound/Ounce	0 lb 7.76 oz x 0.01 oz	0 lb 11.29 oz x 0.01 oz	0 lb 14.81 oz x 0.01 oz	1 lb 5.86 oz x 0.01 oz	2 lb 6.80 oz x 0.01 oz	4 lb 13.60 oz x 0.01 oz
Troy Ounce	7.07 x 0.00005 g	10.29 x 0.00005 g	13.50 x 0.00005 g	19.93 x 0.00005 g	35.36 x 0.00005 g	70.7 x 0.0005 g
Metric Carat	1100 x 0.005 g	1600 x 0.005 g	2100 x 0.005 g	3100 x 0.005 g	5500 x 0.005 g	11000 x 0.05 g
Momme	58.6 x 0.0005 g	84.7 x 0.0005 g	112.0 x 0.0005 g	165.3 x 0.0005 g	293.3 x 0.0005 g	586 x 0.0005 g
Pennyweight	141 x 0.001 g	206 x 0.001 g	270 x 0.001 g	398 x 0.001 g	707 x 0.001 g	1414 x 0.01 g
Grain (UK)	3395 x 0.02 g	4938 x 0.02 g	6481 x 0.02 g	9568 x 0.02 g	16975 x 0.02 g	33951 x 0.2 g
Tael (HK general, Singapore)	5.82 x 0.00005 g	8.47 x 0.00005 g	11.11 x 0.00005 g	16.40 x 0.00005 g	29.10 x 0.00005 g	58.2 x 0.0005 g
Tael (HK jewelry)	5.87 x 0.00005 g	x 0.00005 g	11.22 x 0.00005 g	16.56 x 0.00005 g	29.38 x 0.00005 g	58.7 x 0.0005 g
Tael (Taiwan)	5.86 x 0.00005 g	x 0.00005 g	11.20 x 0.00005 g	16.53 x 0.00005 g	29.33 x 0.00005 g	58.6 x 0.0005 g
Tael (China)	7.04 x 0.00005 g	x 0.00005 g	13.44 x 0.00005 g	19.84 x 0.00005 g	35.20 x 0.00005 g	70.4 x 0.0005 g
Tola (India)	18.8 x 0.0001 g	27.4 x 0.0001 g	36.0 x 0.0001 g	53.1 x 0.0001 g	94.3 x 0.0001 g	188 x 0.001 g
Mesghal	46.9 x 0.0005 g	69.6 x 0.0005 g	89.6 x 0.0005 g	132.2 x 0.0005 g	234.6 x 0.0005 g	769 x 0.005 g

[^] Weighing Chamber

Specifications

	GX-4002A	GX-6001A	GX-6002A	GX-10001A	GX-10002A	
Part#	191701	191705	191702	191706	191704	
List Price	Consult	Consult	Consult	Consult	Consult	
Capacity	4,200 g	6,200 g	6,200 g	10,200 g	10,200 g	
Resolution	0.01 g	0.1 g	0.01 g	0.1 g	0.01 g	
Operating Modes	Animal Weighing, Comparator Function, ACAA Counting Function, Percentage, Density Determination, Statistical Calculation					
Repeatability	0.01 g	0.1 g	0.01 g	0.1 g	0.02 g	
Linearity	±0.02 g	±0.01 g	±0.03 g	±0.01 g	±0.03 g	
Stabilization Time	Approx. 1 second				Approx. 1.5 seconds	
Display Refresh	5 times per second/10 times per second/20 times per second					
Operating Temperature	41° F to 104° F (5° C to 40° C) RH less than 85% (no condensation)					
Pan Size	5 x 5 in (128 x 128 mm)				6.5 x 6.5 in (165 mm x 165 mm)	
Dimensions	(W x D x H) 8.3 x 12.5 x 3.7 in (212 x 317 x 93 mm)					
Est. Ship Weight	11 lb (5 kg)					
Power	120/240VAC adapter, Approx. 30VA					
Warranty	Five-year Limited Warranty					
Return Policy	A&D Weighing Standard Policy - restock fee may apply					
UNIT OF MEASURE	Gram	4200 x 0.01 g	6200 x 0.1 g	6200 x 0.01 g	10200 x 0.1 g	10,200 x 0.01 g
	Ounce (Avoir)	148.1 x 0.0005 g	218 x 0.005 g	218.6 x 0.0005 g	359 x 0.005 g	359.7 x 0.0005 g
	Pound	9.25 x 0.00005 g	13.6 x 0.0005 g	13.66 x 0.00005 g	22.4 x 0.0005 g	22.48 x 0.00005 g
	Pound/Ounce	9lb 4.15 oz x 0.01 oz	13lb 10.69 oz x 0.01 oz	13lb 10.69 oz x 0.01 oz	22lb 7.79 oz x 0.01 oz	22lb 7.79 oz x 0.01 oz
	Troy Ounce	135.0 x 0.0005 g	199 x 0.005 g	199.3 x 0.0005 g	327 x 0.005 g	327.9 x 0.0005 g
	Metric Carat	21000 x 0.05 g	31000 x 0.5 g	31000 x 0.05 g	51000 x 0.5 g	51000 x 0.05 g
	Momme	1120 x 0.005 g	1653 x 0.05 g	1653 x 0.005 g	2720 x 0.05 g	2720 x 0.005 g
	Pennyweight	2700 x 0.01 g	3986 x 0.1 g	3986 x 0.01 g	6558 x 0.1 g	6558 x 0.01 g
	Grain (UK)	64815 x 0.2 g	95680 x 2 g	95680 x 0.2 g	157410 x 2 g	157410 x 0.2 g
	Tael (HK general, Singapore)	111.1 x 0.0005 g	164.0 x 0.005 g	164.0 x 0.0005 g	269.0 x 0.005 g	269.8 x 0.0005 g
	Tael (HK jewelry)	112.2 x 0.0005 g	165.0 x 0.00005 g	165.6 x 0.0005 g	272.0 x 0.005 g	272.5 x 0.0005 g
	Tael (Taiwan)	112.0 x 0.0005 g	165.0 x 0.005 g	165.3 x 0.0005 g	272.0 x 0.005 g	272.0 x 0.0005 g
	Tael (China)	134.4 x 0.0005 g	198.0 x 0.005 g	198.4 x 0.0005 g	326.0 x 0.005 g	326.4 x 0.0005 g
	Tola (India)	360 x 0.001 g	531.0 x 0.01 g	531 x 0.001 g	874.0 x 0.01 g	874 x 0.001 g
Mesghal	896 x 0.005 g	1322 x 0.05 g	1322 x 0.005 g	2176 x 0.05 g	2176 x 0.005 g	