

Capacity: 210g-310g    Readability: 0.001 g

A&D WEIGHING  
**GF-P Series**  
Toploader Balances

## Standard Features

- Pill-counting feature also complies with Handbook 44 requirements
- Fast, Super Hybrid Sensor (SHS) gives you the ultimate in response speed; just one second
- Nine weighing modes
- GLP/GMP/ISO compliance
- WinCT® communication tools software included
- Weighing chamber
- Tough die-cast aluminum housing
- Removable stainless steel pan 5 in x 5 in (127 mm x 127 mm)
- NTEP Certified and Pharmacopoeia approved
- IP54 splash proof operator keyboard protects against dust and spills, stainless steel weigh pan
- Data memory function
- Vacuum Fluorescent Display (VFD)
- RS-232

## APPROVALS



## Specifications

		GF-200P <sup>^</sup>	GF-300P <sup>^</sup>
<b>NTEP</b>	<b>Part#</b>	97799	97800
	<b>List Price</b>	Consult	Consult
<b>Capacity</b>		210g	310g
<b>Resolution</b>		0.001 g	0.001 g
<b>Operating Modes</b>		Weigh, Count and Percent	
<b>Decimal Ounce</b>		7.40755 x 0.00005 oz	10.93493 x 0.00005 oz
<b>Repeatability</b>		0.001 g	
<b>Linearity</b>		±0.002 g	
<b>Stabilization Time</b>		Approx 1 second (typical in FAST mode)	
<b>Operating Temperature</b>		41°F to 104°F (5°C to 40°C)	
<b>Weighing Chamber</b>		3.6 in H (91.4 mm)	
<b>Pan Size</b>		5 x 5 in (127 mm)	
<b>Dimensions</b>		8.27 x 12.48 x 3.39 in (210 x 317 x 86 mm)	
<b>Weight (Approx.)</b>		2.15 lb (4.6 kg)	
<b>Est. Ship Weight</b>		11 lb (5.2 kg)	
<b>Power</b>		110/220V VAC adapter	
<b>Approvals</b>		NTEP CC 04-077 e=0.01g	
<b>Warranty</b>		Five-year Limited Warranty	
<b>Return Policy</b>		A&D Weighing Standard Policy - restock fee may apply	

<sup>^</sup> Weighing Chamber

## Part Number/ Price

Part #	Model #	Description	Price
97799	GF-200P	210g x 0.001 g	Consult
97800	GF-300P	310g x 0.001 g	Consult

## Options/Accessories

Part #	A&D Model #	Description	Price
102891	GX-02	USB option	Consult
97697	GX-10	Glass breeze break for GF-200 and 300	Consult
97703	AX:073003691-S	Protective in-use cover for GF-200/300 (each)	Consult
97649	TB:648	AC adapter (120V/220V) standard with unit	Consult