



Standard Features

- Internal calibration
- Auto environmental compensation
- IP65/NEMA Type 4
- RS-232C bidirectional interface
- Data memory function
- Multiple weighing modes
- Quick reference operation card
- Time and date
- Vacuum Fluorescent Display (VFD)
- Underhook weighing

Specifications

	GX-8K	GX-8K2	GX-10K	GX-12K	
Part#	97776	97775	97777	97778	
List Price	Consult	Consult	Consult	Consult	
Capacity	8.1 kg	8.1 kg/2.1 kg	10.1 kg	12 kg	
Resolution	0.01 g	0.1 g / 0.01 g	0.01 g	0.1 g	
Operating Modes	Counting, Percentage				
Repeatability	0.01 g	0.05 g/0.01 g	0.01 g	0.1 g	
Linearity	±0.02 g	±0.1 g/±0.02 g	±0.03 g	±0.2 g	
Sensitivity drift	±2 ppm/°C	±3 ppm/°C	±2 ppm/°C	±3 ppm/°C	
Stabilization time	Approx 1.5 seconds				
Operating temperature	41° F to 104° F (-5° C to 40° C)				
Pan Size	10.62 x 8.26 in (270 x 210 mm)				
Dimensions	(W x D x H) 11.81 x 13.98 x 4.37 in (300 x 355 x 111 mm)				
Weight	18.3 lb (8.3 kg)				
External Cal mass	2, 3, 4, 5, 6, 7, 8 kg		10 kg	5, 10 kg	
Power	120/240 V AC adapter				
Warranty	Five-year Limited Warranty				
Return Policy	A&D Weighing Standard Policy - restock fee may apply				
UNIT OF MEASURE	Decimal Ounces	285.7190 x 0.0005 oz	285.720 x 0.005/74.0755 x 0.0005 oz	370.4 x 0.0005 oz	423.290 x 0.0005 oz
	Troy Ounce	260.4210 x 0.0005 ozt	260.420 x 0.005/67.5165 x 0.0005 ozt	337.6 x 0.0005 ozt	385.810 x 0.0005 ozt
	Pennyweight	5,208.42 x 0.01 dwt	5,208.4 x 0.1/1350.33 x 0.01 dwt	6,751 x 0.01 dwt	7,716.2 x 0.1 dwt
	Carat	40,500.00 x 0.05 ct	40,500.0 x 0.5/10,500.00 x 0.05 ct	50,500 x 0.05 ct	60,000 x 0.5 ct
	Momme	2,160.000 x 0.005 mom	2,160.00 x 0.05/560.000 x 0.005 mom	2,800.000 x 0.005 mom	3,200.00 x 0.05 mom
	Grain	125,002.2 x 0.2 GN	125,002 x 2/32,408.0 x 0.2 GN	162,040 x 0.2 GN	185,188 x 2 GN
	Pound	17.85745 x 0.00005 lb	17.8575 x 0.0005/4.62970 x 0.00005 lb	23.15 x 0.00005 lb	26.4555 x 0.0005 lb
	Pound/Ounce	17 lb x 0.001 oz	17 lb x 0.001 oz	23 lb x 0.001 oz	26 lb x 0.01 oz

Specifications

	GX-20K	GX-30K	GX-32K	
Part#	97779	97780	97781	
List Price	Consult	Consult	Consult	
Capacity	20 kg	30 kg	30 kg/6.1 kg	
Resolution	0.1 g	0.1 g	1/0.1 g	
Operating Modes	Counting, Percentage			
Repeatability	0.1 g	0.1 g	0.5 g / 0.1 g	
Linearity	±0.2 g	±0.2 g	±1 g / ±0.2 g	
Sensitivity drift (-10 to 30° C)	±3 ppm/° C		±5ppm/° C	
Stabilization Time	Approx 1.5 seconds			
Operating Temperature	41° F - 104° F (-5° C - 40° C)			
Pan Size	10.62 x 8.26 in (270 x 210 mm)			
Dimensions	(W x D x H) 11.81 x 13.98 x 4.37 in (300 x 355 x 111 mm)			
Weight	18.3 lb (8.3 kg)			
External Cal Mass	10, 20 kg	20, 30 kg	20, 30 kg	
Power	120/240VAC adapter			
Warranty	Five-year Limited Warranty			
Return Policy	A&D Weighing Standard Policy - restock fee may apply			
UNIT OF MEASURE	Decimal Ounces	740.755 x 0.005 oz	1,093.495 x 0.005 oz	1,093.50 x 0.05/ 215.170 x 0.005 oz
	Troy Ounce	675.165 x 0.005 ozt	996.675 x 0.005 ozt	996.65 x 0.05/ 196.120 x 0.005 ozt
	Pennyweight	13,503.3 x 0.1 dwt	19,933.5 x 0.1 dwt	19,933 x 1/ 3,922.4 x 0.1 dwt
	Carat	105,000.0 x 0.5 ct	15,5000.0 x 0.5 ct	155,000 x 5/ 30,500.0 x 0.5 ct
	Momme	5,600.00 x 0.05 mom	8,266.65 x 0.05 mom	8,266.5 x 0.5/ 1,626.65 x 0.05 mom
	Grain	324,080 x 2 GN	478,404 x 2 GN	-
	Pound	46.2970 x 0.0005 lb	68.3435 x 0.0005 lb	68.345 x 0.005/ 13.4480 x 0.0005 lb
	Pound/Ounce	46 lb x 0.01 oz	68 lb x 0.01 oz	68 lb x 0.1 oz/13 lb x 0.01 oz

Part Number/Price

Part #	Model #	Description	Price
97776	GX-8K	8.1 kg x 0.01 g	Consult
97775	GX-8K2	8.1/2.1 kg x 0.1/0.01 g	Consult
97777	GX-10K	10.0 kg x 0.01 g	Consult
97778	GX-12K	12 kg x 0.1 g	Consult
97779	GX-20K	20 kg x 0.1 g	Consult
97780	GX-30K	30 kg x 0.1 g	Consult
97781	GX-32K	30/6.1 kg x 1/0.1 g	Consult

Options/Accessories

Part #	A&D Model #	Description	Price
97782	GX-04K*	Comparator/output and RS-232C/20 mA interface	Consult
97783	GX-06K*	Analog output/20 mA interface	Consult
97784	GX-07K**	Waterproof cable for standard RS-232C	Consult
102899	GXK-12	Animal weighing pan	Consult
102898	GXK-31	Draft shield	Consult
97605	AD-100-2	Anti-theft device	Consult
97785	AX-073007197A	Protective in-use cover	Consult
97649	TB:648	AC adapter (120V/220V)	Consult
151247	AD-1688	Data logger	Consult
196128	AD-8127	Impact dot matrix, statistical printer, includes cable	Consult

*GX-04K, GX-06K, replace standard RS-232C and cannot be used at the same time. IP65 rating does not apply when the GX-04K or the GX-06K is installed.

**Use the GX-07K optional waterproof RS-232C cable, in order to use the standard RS-232 interface for water and dust proof (IP65).