Cast Iron

Grip-handle and Nesting Slab Weights

| ASTM CI | ass 6 | | | | | | | Optional |
|----------|--------|--------------------------|--------------------------|--------------------------|--------------------------|-------------------------|---------|---------------------------|
| Weight | Part # | Width | Length | Height | Slot Width | Slot Depth* | Price | Accredited Certificate |
| 3,000 lb | 12872 | 20 3/4in (527.1 mm) | 20 3/4in (527.1 mm) | 29in (736.6 mm) | 3 1/2in (88.9 mm) | 2 3/4 in (69.9 mm) | Consult | Consult |
| 2,500 lb | 12854 | 20 3/4in (527.1 mm) | 20 3/4in (527.1 mm) | 24 3/4 in (628.65 mm) | 3 31/32 in (100.8 mm) | 2 3/4 in (69.9 mm) | Consult | Consult |
| 2,000 lb | 12868 | 20 3/4in (527.05 mm) | 20 3/4 in (527.05 mm) | 19 1/2 in (495.3 mm) | 3 1/2 in (88.9 mm) | 2 3/4 in (69.9 mm) | Consult | Consult |
| 1,500 lb | 12864 | 15 1/8 in (384.2 mm) | 15 1/8in (384.2 mm) | 26 7/8 in (682.6 mm) | 2 1/2 in (63.5 mm) | 2 1/4 in (57.2 mm) | Consult | Consult |
| 1,250 lb | 12858 | 15in (381.0mm) | 15 in (381.0 mm) | 23 3/4 in (603.3 mm) | 2 1/2 in (63.5 mm) | 2 1/4 in (57.2 mm) | Consult | Consult |
| 1,000 lb | 12850 | 15in (381.0mm) | 15 1/2in (393.7 mm) | 18 11/16in (474.7 mm) | 2 3/4 in (69.9 mm) | 2 29/32 in (73.8 mm) | Consult | Consult |
| 500 lb | 12844 | 11 1/2in (292.1 mm) | 12 in (304.8 mm) | 15 3/4 in (400.1 mm) | 2 1/2 in (63.5 mm) | 1 29/32 in (48.4 mm) | Consult | Consult |
| 250 lb | 12892 | 9 3/4 in (247.65 mm) | 9 3/4 in (247.65 mm) | 12in (304.8 mm) | 2 1/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 200 lb | 12890 | 9 3/4 in (247.65 mm) | 9 3/4 in (247.65 mm) | 10 in (254 mm) | 2 1/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 100 lb | 12862 | 9 1/8in (231.8mm) | 7in (177.8mm) | 7 7/8 in (200.0 mm) | 4 1/2in (114.3 mm) | 1 1/2 in (38.1 mm) | Consult | Consult |
| 50 lb | 12839 | 7 29/32 in (200.8 mm) | 5 1/2 in (139.7 mm) | 6 9/16 in (166.7 mm) | 4 1/2in (114.3 mm) | 1 21/32 in (42.1 mm) | Consult | Consult |
| 30 lb | 12878 | 8 1/4in (209.6 mm) | 4 29/32 in (124.6 mm) | 4 1/2in (114.3 mm) | 4 15/32 in (113.5 mm) | 31/32 in (24.6 mm) | Consult | Consult |
| 25 lb | 12833 | 6 1/2in (165.1 mm) | 4 1/2 in (114.3 mm) | 4 15/16 in (125.4 mm) | 3 5/8 in (92.1 mm) | 31/32 in (24.6 mm) | Consult | Consult |
| 20 lb | 12870 | 5 3/4in (146.1 mm) | 4 15/32 in (113.5 mm) | 5 3/32 in (129.4 mm) | 3 31/32 in (100.8 mm) | 1 5/32in (29.4 mm) | Consult | Consult |

| ASTM Clas | ss 7 | | | | | Optional |
|-----------|--------|--------------------|--------------------|----------------------|---------|------------------------|
| Weight | Part # | Width | Length | Height | Price | Accredited Certificate |
| 10 lb | 12828 | 5in (127.0 mm) | 3 1/4in (82.6 mm) | 4 1/32 in (102.4 mm) | Consult | Consult |
| 5 lb | 12823 | 4in (101.6 mm) | 2 9/16in (65.1 mm) | 3 7/32 in (81.8 mm) | Consult | Consult |
| 2 lb | 12874 | 3in (76.2mm) | 2 1/8 in (54.0 mm) | 1 3/4in (44.5 mm) | Consult | Consult |
| 1 lb | 12876 | 2 1/2 in (63.5 mm) | 1 11/16in (42.9mm) | 1 13/32in (35.7 mm) | Consult | Consult |

| Nesting | Slab ASTN | A Class 6 | | | | | | Optional |
|----------|-----------|------------------------|-------------------------|-------------------------|-------------------|------------------------|---------|------------------------|
| Weight | Part # | Width | Length | Height | Slot Width | Slot Depth* | Price | Accredited Certificate |
| 2,500 lb | 12860 | 42 in (1066.8 mm) | 30 in (762 mm) | 8 1/4 in (209.5 mm) | 2 in (50.8 mm) | 2 1/4 in (57.15 mm) | Consult | Consult |
| 1,000 lb | 34563 | 29 1/2in (749.3 mm) | 19 1/2 in (495.3 mm) | 7 1/4 in (184.15 mm) | 2 in (50.8 mm) | 2 1/4 in (57.15 mm) | Consult | Consult |

^{*} Slot depth refers to distance between lifting bars and castings

| Additional Accessories | | | | | |
|------------------------|-----------------------|---------|--|--|--|
| Part # | Description | Price | | | |
| 36092 | Statement of Accuracy | Consult | | | |
| 25836 | Serial number | Consult | | | |



Nesting Slab PN 12860



Cast Iron

Cast IronGrip-handle Weights

| ASTM CI | ass 6 | | | | | | | Optional |
|----------|--------|--------------------------|--------------------------|-----------------------|--------------------------|-------------------------|---------|---------------------------|
| Weight | Part # | Width | Length | Height | Slot Width | Slot Depth* | Price | Accredited Certificate |
| 1,000 kg | 12801 | 20 1/2 in (520.7 mm) | 20 1/2 in (520.7 mm) | 22 in (558.8 mm) | 3 1/2 in (88.9 mm) | 2 3/4 in (69.85 mm) | Consult | Consult |
| 500 kg | 12797 | 15 1/8 in (384.2 mm) | 15 1/8 in (384.2 mm) | 20 3/4 in (527 mm) | 2 1/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 250 kg | 12782 | 11 1/2 in (292.1 mm) | 12 1/2 in (317.5 mm) | 17 1/2 in (444.5 mm) | 2 1/2 in (63.5 mm) | 1 7/8 in (47.6 mm) | Consult | Consult |
| 200 kg | 12793 | 11 1/2 in (292.1 mm) | 12 in (304.8 mm) | 14 1/4 in (362 mm) | 2 1/2 in (63.5 mm) | 1 7/8 in (47.6 mm) | Consult | Consult |
| 100 kg | 12817 | 9 7/8 in (250.8 mm) | 9 7/8 in (250.8 mm) | 11 in (279.4 mm) | 2 1/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 50 kg | 12803 | 9 7/32 in (234.2 mm) | 7 in (177.8 mm) | 8 13/16 in (223.8 mm) | 4 15/32 in (113.5 mm) | 1 29/32 in (48.4 mm) | Consult | Consult |
| 35 kg | 12805 | 7 7/8 in (200.0 mm) | 5 1/2 in (139.7 mm) | 9 15/32 in (252.4 mm) | 4 15/32 in (113.5 mm) | 1 1/16 in (27.0 mm) | Consult | Consult |
| 25 kg | 12775 | 7 21/32 in (194.5 mm) | 5 1/2 in (139.7 mm) | 7 3/32 in (180.2 mm) | 4 7/16 in (112.7 mm) | 1 13/16 in (46.0 mm) | Consult | Consult |
| 20 kg | 12771 | 7 5/8 in (193.7 mm) | 5 19/32 in (142.1 mm) | 5 29/32 in (150.0 mm) | 4 5/8 in (117.5 mm) | 1 19/32 in (40.5 mm) | Consult | Consult |
| 10 kg | 12767 | 6 in (152.4 mm) | 4 1/2 in (114.3 mm) | 5 in (127.0 mm) | 3 3/4 in (95.3 mm) | 1 1/16 in (27.0 mm) | Consult | Consult |

| ASTM CI | ass 7 | | | | | Optional |
|----------------|--------|-----------------------|----------------------|----------------------|---------|---------------------------|
| Weight | Part # | Width | Length | Height | Price | Accredited Certificate |
| 5 kg | 12786 | 5 15/32 in (138.9 mm) | 3 13/32 in (86.5 mm) | 4 1/8 in (104.8 mm) | Consult | Consult |
| 2 kg | 12809 | 3 31/32 in (100.8 mm) | 2 9/16 in (65.1 mm) | 2 13/16 in (71.4 mm) | Consult | Consult |
| 1 kg | 12813 | 3 in (76.2 mm) | 2 1/8 in (54.0 mm) | 1 27/32 in (46.8 mm) | Consult | Consult |
| 500 g | 12815 | 2 1/2 in (63.5 mm) | 1 5/8 in (41.3 mm) | 1 17/32 in (38.9 mm) | Consult | Consult |

| OIML CI | ass M1 | | | | | | | Optional |
|---------|--------|-----------------------|--------------------------|--------------------------|--------------------------|-------------------------|---------|---------------------------|
| Weight | Part # | Width | Length | Height | Slot Width | Slot Depth* | Price | Accredited Certificate |
| 500 kg | 156304 | 15 1/8 in (384.2 mm) | 15 1/8 in (384.2 mm) | 20 3/4 in (527 mm) | 21/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 250 kg | 156305 | 11 1/2 in (292.1 mm) | 12 in (304.8 mm) | 17 1/2 in (444.5 mm) | 21/2 in (63.5 mm) | 1 7/8 in (47.6 mm) | Consult | Consult |
| 100 kg | 156306 | 9.87 in (250.7 mm) | 9.87 in (250.7 mm) | 11 in (279.4 mm) | 21/2 in (63.5 mm) | 2 in (50.8 mm) | Consult | Consult |
| 50 kg | 105417 | 9 7/32 in (234.2 mm) | 7 in (177.8 mm) | 8 13/16 in (223.8 mm) | 4 15/32 in (113.5 mm) | 1 29/32 in (48.4 mm) | Consult | Consult |
| 20 kg | 105416 | 7 5/8 in (193.7 mm) | 5 19/32 in (142.1 mm) | 5 29/32 in (150.0 mm) | 4 5/8 in (117.5 mm) | 1 19/32 in (40.5 mm) | Consult | Consult |
| 10 kg | 105415 | 6 in (152.4 mm) | 4 1/2 in (114.3 mm) | 5 in (127.0 mm) | 3 3/4 in (95.3 mm) | 1 1/16 in (27.0 mm) | Consult | Consult |
| 5 kg | 105414 | 5 15/32 in (138.9 mm) | 3 13/32 in (86.5 mm) | 4 1/8 in (104.8 mm) | - | - | Consult | Consult |

^{*} Slot depth refers to distance between lifting bars and castings

| Additional Accessories | | | | | |
|------------------------|-----------------------|---------|--|--|--|
| Part # | Description | Price | | | |
| 36092 | Statement of Accuracy | Consult | | | |
| 25836 | Serial number | Consult | | | |



Grip-handle